## (12) 法风专用合作统约所公布的图际中面

## (19) 做界知识产权组织 國際口



## 

(43) 园际公布日: 2003477 A 10 B (10.02.2005)

PCI

(10) 西原公布号: WO 2005/013527 A1

· (SI)_BIS\$297':	. Heal-Bros-Hoas	HEXULIZA02-HEXB-1190.	
(21) <u>M</u> F <del>+</del> <del>1</del>	PCTACHZARAF00001		
(22) BC + + + + + + + + + + + + + + + + + +	2003-F7 A 29 A (ZD.07.2003)		
(29) රච්ච්රිය:		ቁ የ	
(26) 公安哲心:		ĸ	
(30) <b>ALLEA</b> : 031097659	20034¥3 A 3 B (05.00.2003)	CN CN	


- (71) POAMBUREUN MARTAREDE XOUSION RETIRAÇÃO TANO MOBILO COMMUNICATIONS EQUIPMENT CO. LTD.) ICNICNI: PELE BUREU PERAS. DONOS 162030 (CN).
- (71) ICA:A (75) ICA-PA(MBIE): ECH(WANG, Ymaeb) (CACH): BIE(YANG, COMINE) [CNCN]: ISEA (SUR, Charges) [CNCN]: PELLE FIREFR (AVG, Belling (CN).
- (74) RELA: LICENSERPERREUMS & GODEON INTELLECTUAL PROPERTY LAW CORPORATION: PERINGER WELLIGHT CORPORATION: PERINGER WELLIGHT COLLIGH, BAJING 1002D (CM).

- (81) AT MANGAT, AT CONTEMBER BETT P.
  AL, AG, AL, ANG, AT, AU, AZ, BA, BB, BG, BR, BW,
  BY, BZ, CA, CR, CN, CD, CR, CU, CZ, BL, BK, BM,
  BZ, CG, BL, BG, BS, FI, GE, GD, GL, GM, GM, MR,
  BU, ID, L, IN, ES, JP, ML, KG, KF, KL, IZ, LC,
  LK, LR, LS, LT, LU, LV, MA, MD, MG, ML, MN,
  MY, MI, MZ, NA, NI, NO, NZ, ON, PG, PH, PL,
  PT, EO, EU, SC, SD, SE, SC, SK, SL, SY, FJ, TM,
  TN, TT, TT, TZ, UA, UG, US, UZ, VC, YN, YU, ZA,
  ZM, ZW
- (C) DRE(DB VAG, TX4—HVERSCEOKOP): ANDOCOV, CB. CM. KB. LS. MW. MZ. NA. SD. SL. SZ. TZ. UG. ZM. ZV). CET VIJ(AM, AZ. BY. KG. KZ. MD. RU. TJ. TM. CTQ VI(AT. BE. BG. CH. CY. CZ. DI. DK. EB. ES. FI. FIL. GB. CE. HU. II. II. LU. MC. NL. PL. TT. RO, SB. SI. SK. TR). OAPI(BT. LJ. CT. CG. CI. CM. CA. CM. GQ. CW. KIL, ME. NE. SN. TO, TG)

수민무**소**당: — 실험된 5022 [[다.

历马周双子个代码和北京公司第5· 1000和亚亚马马 PCT全国周南通路中代西里西河南与门马克河。

(50) Time: Mithod for Detrecting the Orthogonal Code Coma Signal BO 2040: ERRODMANGOLITE



- CONTROL CARRELLA C

(37) Abstract: The present invention discloses a method for detecting the explosional each CDMA disput, it mainly includes: extracting the arm power of each multipath sugard and performing near propertion combination by using the power of each multigath signal a dictioner, in order to get optimized matched littering culput; and writed detecting the optimized cratched filtering output. It may be two implement: when using the datest implement of spitialized mulched filtering, at only needs to perform the first two main etero; when using the usual detecting implement, it needs to perform all the three ctops. For the two implements extinute the main power of each multipath signal o disturber, it needs to extent the durant code o chemnal which join to examinon, namely calcus oil the code's channel of this substance of this substance which not purform called detection. At a regult of work the orthogonal code characteristic and characteristic estimation, improve the orthogonal performance by small coal. It can be expectally used in the device of enhagenal code COMA system.